

In the Claims:

Please amend claim 1. The status of the claims is as follows:

1. (Currently Amended) A pneumatic tire comprising:

a plurality of circumferential grooves extending in a tire circumferential direction in a tread surface having a width and a circumferential center;

a plurality of lateral grooves extending from the circumferential grooves away from the circumferential center of the tread surface, the lateral grooves being open at their distal ends from the circumferential center of the tread surface and provided intermittently in the tire circumferential direction; and

line portions provided in a wall face of the circumferential grooves, the line portions being composed of a plurality of ridges or recesses that are inclined from approximately 10° to 60° less than 45° with respect to ~~a groove longitudinal the tire circumferential~~ direction, ~~along a plane substantially parallel to the tread surface~~;

wherein the line portions are provided in a range of not less than 50% of the wall face of the ~~longitudinal~~ circumferential grooves in a cross section of the longitudinal grooves orthogonal to the groove longitudinal direction.

2. (Cancelled)

3. (Previously Presented) The pneumatic tire according to claim 1, wherein a height of the line portions is not smaller than 0.3 mm and is not more than 20% of each of a width and depth of the circumferential grooves.

4. (Previously Presented) The pneumatic tire according to claim 1, wherein a pitch interval of the line portions is 1.5 to 8.0 mm.

5. (Cancelled)